

# Orient & Orient 2



## features & benefits

*The elegance and simplicity of the Orient in a double sided banner stand! That's the Orient 2. Dual retractor mechanisms allow you to present two graphics back to back. It is finished in Anodized Silver with heavy duty molded end plates. Padded carry bag is included.*

### Double sided

Orient 2 (31.5w) - ONT-800-DBL-S

Orient 2 Grande (39.25w) - ONT-1000-DBL-S

### Single sided

Orient (31.5w) - ONT-800-S

Orient Grande (39.25w) ONT-1000-S

# LetterBank

hardware specifications	graphic specifications	additional info
<p>Height: 84"                      Orient &amp; Orient 2 31.5w                      Orient &amp; Orient 2 Grande 39.25w                      Unit Footprint 800/1000:                      32 1/2" x 9 9/16" / 40 3/8" x 9 9/16"</p>	<p>Orient Graphic size: 31.5"W x 84"H                      (+ 6" bleed).                      Orient Grande Graphic size: 39.25"W x 84"H                      (+ 6" bleed).                      Orient 2 Graphic size: 31.5"W x 84"H                      (+ 6" bleed)                      Orient 2 Grande Graphic size: 39.25"W x 84"H                      (+ 6" bleed)                      Substrate Dimensions 800/1000:                      31 1/2" x 90 1/2" / 39 1/4" x 90 1/2"</p>	<p>Approx weights w bag 800/1000:                      16 lbs. / 18 lbs.                      Shipping Dimensions: 35"x12"x6"                      Bag Dimensions 800/1000:                      33 1/2"x 10 1/2" x 4" / 41" x 10 1/2" x 4"</p>

We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE.

# Assembly Instructions




Remove doubler from the velcro pocket and the pole from the pole pocket



Remove pole from plastic bag



Assemble pole



Attach doubler to the top of the pole



Place pole into the units pole socket.



Tilt the unit toward yourself while raising the graphic to the top of the pole



Attach the graphic rail to the doubler



Repeat steps 7 & 8 for the second graphic



Reverse the procedure to disassemble